



SND-2 Series

Exhaust Only Hood

CaptiveAire's Premier Sloped Canopy Hood

The SND-2 Series is a Type I, Sloped Wall Canopy Hood for use over 400°F and 600°F cooking surface temperatures. The Sloped Canopy is the ideal hood choice for low ceiling heights.


Fully Integrated Package

CaptiveAire sells this hood as a stand-alone appliance to be integrated into a kitchen ventilation application, or provided as part of a FULLY INTEGRATED PACKAGE designed by CaptiveAire and pre-engineered for optimum performance. The package consists of the hood, an integral utility cabinet, factory pre-wired electrical controls, and a listed fire suppression system. Other options include a listed exhaust fan, a listed make-up air unit and listed, factory-built ductwork.

Advantages

- ▶ **Exhaust Flow Rates:** Superior exhaust flow rates.
- ▶ **ETL Listed:** ETL Listed for use over 400°F and 600°F cooking surface temperatures, which provides flexibility in designing kitchen ventilation systems. ETL Listed to US and Canadian safety standards, ETL Sanitation Listed and built in accordance with NFPA 96.
- ▶ **Capture and Containment:** Insulated, double-wall rigid front has aerodynamic design that reduces radiant heat into kitchen, prevents condensation and provides exceptional capture and containment of cooking vapors. The signature "mechanical baffle" on the front of the hood's capture area is available on 18" Front Model only. The mechanical baffle provides a built-in wiring chase for optimal positioning of electrical controls and outlets on the front face of the hood without penetrating capture area or requiring external chase way.
- ▶ **Convenient Design:** Factory pre-wired lighting to illuminate the cooking surface is accessible from the bottom of the hood. Fitted with UL Listed, pre-wired, incandescent light fixtures and tempered glass globes to hold up to a standard 100 watt bulb. Pre-punched hanging angles on each end of hood and additional set provided for hoods longer than 12'.
- ▶ **Construction:** Polished stainless steel on the interior and exterior of the front enhance aesthetics. Fully welded and polished front corners. Fabricated from Type 430 stainless steel with option of Type 304 available. Sloped front for low ceiling applications.
- ▶ **Grease Extraction:** All hoods come standard with stainless steel baffle filters and a deep grease trough which allows for easy cleaning. Captrate Combo® and Captrate Solo® filters are optional. Grease drain system with removable 1/2 pint cup for easy cleaning. Standard filter stops eliminate gaps between filters.
- ▶ **Reduced Lead Times and Shipping Costs:** Produced on a high volume assembly line at one of five manufacturing facilities to reduce lead times and shipping costs.
- ▶ **Controls:** Hoods can be equipped with modular utility cabinets and end standoffs. Optional listed light and fan control switches flush mounted and pre-wired through electrical chase way.
- ▶ **Reduced Weight:** Rigid single wall end panels reduce weight.
- ▶ **Optional Make-Up Air:** Make-up air can be supplied through optional front and/or side plenums (ND-2 Series with PSP or AC-PSP Accessory).
- ▶ **Optional Self Cleaning Technology:** The Self Cleaning Hood option adds a spray bar that extends the full length of the hood immediately behind the filters. The system cleans grease from the plenum and portion of the duct with the daily hot water spray cycle.
- ▶ **Optional CORE Protection:** The CORE Fire Protection System is an automatic, pre-engineered fire suppression system which is ETL listed to UL Standard 300. The CORE Protection System is designed to provide primary coverage for ventilating equipment including hoods, ducts, plenum and filters.

Features



Performance

AVG. COOKING SURFACE TEMP.(°F)	CONFIGURATION	MIN EXHAUST CFM/FT.
400°F	Single Wall Hood 2 Wall Hoods Back-to-Back	228 456
600°F	Single Wall Hood 2 Wall Hoods Back-to-Back	294 588

Recommended Duct Sizing: Exhaust - Based on 1500 FPM

Options

Utility Cabinet: Listed for integral side mount and fabricated of same material as hood. Cabinet can house listed fire suppression system and listed, pre-wired electrical controls.

Front Perforated Supply Plenum: Provides low velocity make-up air for the kitchen and is discharged in front of the hood. Perforated diffuser plates allow for even air distribution and supply riser includes a volume damper for easy balancing. Side Perforated Supply Plenums can be added to optimize the air flow if necessary.

Enclosure Panels: Constructed of stainless steel. Sized to extend from hood top to ceiling, enclosing pipe and hanging parts.

End Panels: Should be used to maximize hood performance and eliminate the effects of cross drafts in kitchen. units constructed of stainless steel and sized according to hood width and cooking equipment. Exposed edges hemmed for safety and rigidity.

Roof Top Package: Combination ETL Listed exhaust/supply air unit with factory prewired and mounted motors, trunkline and curb vented on exhaust side.

Separate Exhaust and/or Make-Up Air Fans: ETL Listed single exhaust fans and supply-air fans and curbs available.

Fire Suppression System: UL 300 fire suppression system.

Lighting: Recessed Incandescent, Recessed Fluorescent, Compact Fluorescent, Recessed LED, Halogen

Certifications

The SND-2 Model has been certified by ITS. This certification mark indicates that the product has been tested to and has met the minimum requirements of a widely recognized (consensus) U.S. and Canadian products safety standard, that the manufacturing site has been audited, and that the applicant has agreed to a program of periodic factory follow-up inspections to verify continued performance.

Models SND-2 are ETL Listed under file number 3054804-001 and complies wwith UL710, ULC710 and ULC-S646 Standards.



Intertek