



# EX-BS-N Series

## Exhaust Only Hood

Low Proximity Exhaust Hood with Plate Shelf

The EX-BS-N Series is a Type I, Low Proximity Passover Hood for use over 600°F cooking surface temperatures. A plate shelf is integrated into the hood for space saving, compact design.

### Fully Integrated Package

CaptiveAire sells this hood as a stand-alone appliance to be integrated into a kitchen ventilation application, or provided as part of a FULLY INTEGRATED PACKAGE designed by CaptiveAire and pre-engineered for optimum performance. The package consists of the hood, an integral utility cabinet, factory pre-wired electrical controls, and a listed fire suppression system. Other options include a listed exhaust fan, a listed make-up air unit and listed, factory-built ductwork.



### Advantages

- **Superior Exhaust Rates:** Low exhaust CFM requirements.
- **ETL Listed:** ETL Listed for use over 600°F cooking surface temperatures. ETL Listed to US and Canadian safety standards, ETL Sanitation Listed and built in accordance with NFPA 96.
- **Convenient Design:** Space saving, compact design uses limited kitchen space. Plate shelf incorporated into the hood to meet application needs.
- **Construction:** Fabricated of Type 430 stainless steel, #3 or #4 polish, on all exposed surfaces. Optional type 304 stainless steel available. Pre-punched hanging angles on each end of hood. Additional set provided for hoods longer than 12'.
- **Grease Extraction:** Fitted with aluminum baffle filters, removable for cleaning. Optional stainless steel baffle and high efficiency stainless steel baffle filters are available. Sloped grease drain system with removable 1/2 pint cup for easy cleaning.

### Performance

600°F Cooking Surface - Ovens, Steamers, Kettles Open-Burner Ranges, Griddles, Fryers

Model	Type	Min. Exhaust CFM/ft.
EX-BS-N	Wall hood	250

## Options

**Enclosure Panels:** Constructed of stainless steel. Sized to extend from hood top to ceiling, enclosing pipe and hanging parts.

**Roof Top Package:** Combination ETL Listed exhaust/supply air unit with factory prewired and mounted motors, trunkline and curb vented on exhaust side.

**Separate Exhaust and/or Make-Up Air Fans:** ETL Listed single exhaust fans and supply-air fans and curbs available.

**Fire Suppression System:** UL 300 fire suppression system.

## Certifications

The EX-BS-N Model has been certified by ITS. This certification mark indicates that the product has been tested to and has met the minimum requirements of a widely recognized (consensus) U.S. and Canadian products safety standard, that the manufacturing site has been audited, and that the applicant has agreed to a program of periodic factory follow-up inspections to verify continued performance.

Model EX-BS-N is ETL Listed under file number 3054804-001 and complies with UL710, ULC710 and ULC-S646 Standards.

